

Xerox® WorkCentre® 5755 Multifunction Printer



WorkCentre 5755 shown with Duplex Automatic Document Handler, High Capacity Tandem Tray, Offset Catch Tray, Work Shelf and Convenience Stapler.



WorkCentre 5755 shown with Duplex Automatic Document Feeder, High Capacity Tandem Tray, Office Finisher, Work Shelf and Convenience Stapler.

System Specifications			
Speed (up to) 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	Up to 55 ppm Up to 36 ppm Up to 31 ppm		
Monthly Duty Cycle¹	Up to 200,000 pages		
Hard Drive / Processor / Memory	160 GB hard drive shared / 1.2 GHz Freescale dedicated / 640 MB (expandable to 1 GB with additional Memory Kit)		
Connectivity	Ethernet 10/100/1000 Base-T, IEEE802.5 (Token Ring) [via third-party adapter], Wireless Ethernet (IEEE802.11a/b/g) [via third-party adapter], USB print		
Copy Specifications			
Copying			
First-copy-out Time	As fast as 3.4 seconds		
Document Scanner	Duplex Automatic Document Handler (DADH) 100-sheet capacity Scans sizes up to 11 x 17 in. (A3/297 x 420 mm) SEF		
Sides (input:output)	1:1, 1:2, 2:2 and 2:1		
Quantity	1 to 9,999		
Resolution	600 x 600 dpi input / 4800 x 600 dpi interpolated output		
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)		
Copy Pre-Collation Memory (EPC)	384 MB (expandable to 1 GB with additional Memory Kit)		
Basic Copy Features/ Options	<table border="0"> <tr> <td> Features: Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching </td> <td> Options: Hole Punching Stapling </td> </tr> </table>	Features: Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching	Options: Hole Punching Stapling
Features: Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching	Options: Hole Punching Stapling		
Imaging Copy Features	Image Quality • Original Type Selections: Normal, Text, Halftone, Photo • Output Quality Selections: Lighter/Darker, Background Suppression, Contrast, Sharpness or Screening Book Copying/Bound Copying Edge Erase (with Print to Edge option) Mixed Size Original Image Shift (with Auto Center option)		
Output Copy Features	ID Card Copy Booklet Creation Inserts and Tab copying Covers (Front only, Front and Back, Back only: Blank or Printed) Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Annotation and Bates Stamping Multi-up (up to six columns by six rows) Invert Image (negative or mirror image) Sample Set and Job Storage (Store and Recall job programming) Transparencies (including dividers – blank or printed) Heavy weight paper (not rough stock)		

Other Copy/Device Features	Job Interrupt (Interrupt the current job) Help (Intuitive text and graphic descriptions) Onboard Documentation Languages (Select up to 21 languages for User Interface – US English, International French, Italian, German, International Spanish, Catalan, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)* * Language selection and number varies by location
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Six User-Programmable percentages (25%, 64%, 78%, 129%, 154% and 200%)
Foreign Device Interface (FDI) (Optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox® Custom Application Service
USB Port	Xerox® Copier Assistant® Customer device administration/software upgrade Common Access Card Enablement
Accessibility Option	Xerox® Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.
Paper Handling – Duplex Automatic Document Feeder (DADF)	
Capacity²	100 sheets
Speed 8.5 x 11 (A4/210 x 297 mm) LEF	Up to 80 ipm
Paper Sizes Sensed	Statement – 5.5 x 8.5 in. (A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) Letter – 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF Legal – 8.5 x 14 in. (216 x 356 mm) SEF Ledger – 11 x 17 in. (A3/297 x 420 mm) SEF
Weights	13 lb to 42 lb bond (50 to 160 gsm)
Paper Handling – Trays 1-2	
Capacity²	500 sheets each
Sizes	User Adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Tab Stock Bond Custom Settings (up to 7)
Options	Envelope Tray Kit for Tray 2 (Capacity 50 envelopes)
Paper Handling – Bypass Tray	
Capacity²	100 sheets
Sizes	Custom sizes: 4.25 x 5.5 in. (A6) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 58 lb bond (60 to 216 gsm)
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Label Stock Transparencies Tab Stock Bond Custom Settings (up to 7)
Paper Handling – High Capacity Tandem Tray (Standard)	
Capacity²	Two trays: 1,600 and 2,000 sheets
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)

Paper Handling – High Capacity Feeder (Optional)	
Capacity ²	4,000 sheets
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF Optional 8.5 x 11 / 8.5 x 14 Short Edge Feed Kit – 8.5 x 14 in. (A4/210 x 297 mm) SEF with 2,000 sheet capacity Optional 11 x 17 Short Edge Kit – 11 x 17 in. (A3/297 x 420 mm) SEF with 2,000 sheet capacity
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
Paper Handling – Total Capacity	
Device Total Capacity ²	8,700 sheets (with Bypass Tray, front loading paper trays, High Capacity Tandem Tray and High Capacity Feeder)
Output Option - Offset Catch Tray (Optional)	
Capacity ²	300 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Output Option – Office Finisher (Optional)	
Capacity ²	Top Tray – 250 sheets Stacking Tray – 2,000 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Stapling ²	50 sheets Single (any corner) and dual
Hole Punch (Optional)	3-hole punch 2-hole Legal punch
Output Option – Convenience Stapler Option	
Capacity ²	50 sheets
Print Specifications	
Network Printing – Controller (Simultaneous rip, receive, program ahead, queue processing and transmit)	
Printer Language (PDL) auto switching	<ul style="list-style-type: none"> • PCL 6/PCL 5e • PostScript 3 emulation • TIFF (6.0 Old JPEG and New JPEG) • TIFF Fax Extended (TIFF-FX) • PDF • LCDS, SCS, XES and IPDS through third party transforms
Network Printing – Resolution (printing via Xerox® CentreWare® software)	
	PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey) PCL: 600 x 600 dpi Supports PCL and PS switching within job
Network Printing – Printing Features	
Advanced features	Bi-directional Print Drivers Embedded web server for remote control/monitor/setup Job monitoring at the device and at desktop
Paper Output	Special font, Banner Sheet, Rotate Image, Offset
Network Printing – Print Driver Options	
Paper Output	Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay • LAN Fax-with fax option • Save and Save & Print Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch (if configured) • Booklet creation • Fit to new paper size Output tray selections Store and recall driver setting
Special Pages	Exception Page programming (covers, inserts/tabs, exception pages)

Image Options	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins (edge to edge printing) Invert Image (negative/mirror)		
Layout/Watermark	N-up (16) / Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark options		
Printing Protocols and Networks			
Physical	Ethernet 10/100/1000Base-T, IEEE802.5 (Token ring) [via third party adapter], Wireless Ethernet (IEEE802.11a/b/g [via third party adapter], USB print		
Operating Systems	<ul style="list-style-type: none"> • Microsoft® Windows®, Vista, Windows 7, Windows Server 2003, Windows Server 2008 • Novell® NetWare 5.x, 6.x • Mac® OS® 10.4, 10.5, 10.6 • Solaris 8, 9, 10 SPARC, Solaris 10x86 • HP-UX® 11iv2 • IBM® AIX 5 v5.3 • Linux Fedora Core 1-9 • Red Hat® Enterprise Linux® 4 • open SUSE® 10/11 		
Network Protocols	<ul style="list-style-type: none"> • TCP/IPv4/IPv6, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP • AppleTalk/EtherTalk 		
Administration Protocols	DHCP, BOOTP, SNMP, WINS, Bonjour, DDNS, SLP v2, SSDP, HTTP/S, RARP, LDAP, SMTP, POP3		
Security Protocols/Features	Protocols <ul style="list-style-type: none"> • HTTPS • IPsec • 802.1X • SNMPv3 	Features <ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Data Encryption 	
Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts) PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	Environment Windows 7, Windows Server 2003/2003 64 Bit, Windows Vista/Vista 64 Bit, Windows Server 2008, Microsoft Certified	PCL6/5e Xerox® custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs 	PostScript 3 Xerox® custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs
	Mac OS 10.4 - Generic PPD	N/A	Generic PPD
	Mac OS 10.5, 10.6 - Xerox® custom	N/A	Xerox® custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Toner, Fuser and Xerographic module status
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Xerox® Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Print Submission Tools	Environment Solaris 8, 9, 10 SPARC, Solaris 10x86; HP-UX® 11.0, 11iv2, IBM® AIX 5 v5.3; Linux Fedora Core 1-9; Red Hat® Enterprise Linux® 4; open SUSE® 10/11	PCL N/A	PostScript 3 Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows® Server 2003, Windows Server 2008, Windows Vista	N/A	Submission Tool for any TIFF or PDF file (via web only)

Device Management	
Management Support	SNMP Version 1, SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2
Xerox® CentreWare® Internet Services	Allows simple remote installation setting of configuration options and management of the device.
Xerox® CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows 2003 and Internet Explorer 6.0 and higher.
Novell NDPS/NEPS (gateway for WorkCentre)	Server gateway application: centralized management tool
Xerox® CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View.
Xerox® CentreWare for Tivoli NetView	Provides for the identification of Xerox® WorkCentre multifunction systems in the general discovery performed by Tivoli NetView.
Xerox® CentreWare for HP OpenView	Provides for the identification of Xerox® WorkCentre multifunction systems in the general discovery performed by HP Openview. Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView.
Xerox® Barcode Pro PS Information available at www.xeroxofficesap.com	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
Xerox® Device Types for SAP R/3 Environment are available at www.xeroxofficesap.com	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre • Network Accounting (JBA) – Provides capability to add Job Based Accounting User IDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox® standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox® Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
Xerox® SAP R/3 Intelligent Barcode Utility (optional) Purchase via www.font.net	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP R/3 environment and Xerox® Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.
CentreWare Internet Services – Integrated device Web page	
Device Status	Web server embedded on Controller <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job-Print Queue Viewing	Complete job print queue management
Job Submission	Print ready files PS, PCL (TIFF, PDF with Copier/Printer only) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Scan Template Management	250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning
Browsers	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x, 7.x Safari 1.x Mozilla Firefox 1.x
Support	Online support available via web page

Scan Specifications	
Scanning	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
Speed 8.5 x 11 (A4/210 x 297 mm) LEF	Up to 80 ipm
Resolutions	DPI Options 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
	Scan Presets <ul style="list-style-type: none"> • Archival Record (Normal Quality - Smallest file size) – 100 x 100 • For Sharing and Printing (Normal Quality - Small file size) – 200 x 200 • For High Quality Printing (High Quality - Large file size) – 300 x 300 • For OCR (High Quality - Large file size) – 300 x 300 • Simple Scan (Normal Quality - Small file size) – 200 x 200
	Quality/File Size <ul style="list-style-type: none"> • Normal Quality (Small file size) • Higher Quality (Large file size) • Maximum Quality (Largest file size)
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
File Formats	TIFF 6.0 with G3 MH, G4 MMR or JPEG compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression), PDF/A, XPS, Searchable PDF, PDF/A Searchable XPS
Network Scanning	
Capability	<ul style="list-style-type: none"> • Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services • Scan to Home displays one template and populates with the user's directory path after authentication • Scan to file • Scan to network server / directory • Scan to Mailbox • Scan to Folder on hard disk for device access of documents • Color scanning (optional)
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template • Metadata Fields consists of field name, display at the LUI or not, default value and other configurations Customized fields viewed on user interface Variable data entered using virtual keyboard at device
Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job for Scan to file and Scan to Email (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge.
Scan to Email	
Capability	Scan to Email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare Internet Services confirmation sheet options
Network Scanning Software Solutions	
Xerox® Scan to PC Desktop® Workgroup Edition SE (optional)	A desktop offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort SE – image viewing and file management software ScanSoft OmniPage SE – offer desktop/client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre to individual desktops
Scan to PC Desktop Workgroup Edition Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools. ScanSoft PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> • Complete PDF functionality • Secure PDF workflow of all scanning applications ScanSoft OmniPage Pro Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes an email inbox polling capability.

Fax Specifications	
Fax Options – Walkup Option (One or Two Lines Options)	
Compatibility	ITU (CCITT) Group 3
Memory	256 MB (One Line and Two Line options)
Speed/Modem(s)	1 or 2 V.34 modems: 33 kbps. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/JBIG/G3/Super G3
Fax Send Features	Quality/Resolution <ul style="list-style-type: none"> • Original type: Normal, text, half tone, photo, lighter/darker, background suppression • Fax – off Platen, mixed sizes or Bound/Book Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce/Split large documents Cover letter Delayed send Build Job (up to 1000 images) Polling
Fax Receive Features	One- or two-sided printing Stapled or unstapled, hole punch Receive print mode – Manual (size, margin, stock, header)/Auto Auto answer delay Secure receive Junk fax prevention Fax Forward to Email and File
Fax Reports	Activity Dial directory Group directory Options Pending Jobs
Fax Mailboxes	Up to 100 password-protected Poll Remote mailboxes (up to 255) password-protected
Auto Dialing Features	Speed Dials <ul style="list-style-type: none"> • 200 (One-line option) • 1,000 (Two-line option) Group Dials: One-line Option: <ul style="list-style-type: none"> • Up to 100 groups • Up to 200 recipients per group • Up to recipient entries: 200 Two-line option: <ul style="list-style-type: none"> • Up to 200 groups • Up to 400 recipients per group • Up to 1000 recipient entries Auto redial <ul style="list-style-type: none"> • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)
Resolutions	200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi 200 x 400 dpi 400 x 400 dpi 400 x 600 dpi 600 x 600 dpi (Super Fine)
Fax Options – LAN Fax with Walkup Fax (Optional)	
	Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers) Recipient options (add recipient or add from phone book) User personal phone book – up to 1,000 entries Confirmation sheet Send speed (14.4/33.6kbps or 4800bps) Send time Dialing options (prefix or credit card) Cover sheet (add notes) Preferences – Phonebook (personal or shared LDAP)

Fax Options – Internet Fax Enablement (Standard)	
Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi
Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T T.37 compliant
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body
Fax Options – Network Fax Server Enablement (Standard)	
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
Maximum Scan Size	11 x 17 in. (A3/297 x 420mm)
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. (A3/297 x 420 mm)) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox® Alliance Partner Program. For details visit www.xerox.com
Device Management Specifications	
Accounting Features – Xerox® Standard Accounting	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User Id) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter Xerox® Standard Accounting ID into the print driver when submitting a print job, similar to secure print. Xerox® Standard Accounting can be used in conjunction with an external device via the Foreign Device Interface (e.g. Coin Op or Card Reader).
Accounting Features – Network Accounting Enablement Kit	
	Enhanced network accounting with up to the minute data on how the system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox® Business Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from 3rd party server enabling larger databases of users and accounts

Security – Review the Supplemental Security Brochure for Details	
Authentication	Secure device login with network user name and password Supports Kerberos (Windows® 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) LDAP
Features	802.1X Compliant IPv6 Ready (Phase 2) Disk Image Overwrite – Immediate, On Demand, Scheduled HTTPS (SSL) SNMP V3 IPsec Network Authentication Device Access Password Protection IP Filtering Audit Log Full Disk Encryption Secure Print Fax Security
Common Access Card Enablement	
	Common Access Card Enablement is a solution that increases security of government facilities and critical information through the use of smart identification cards. (Available only in U.S. and certain configurations.)
Xerox Extensible Interface Platform®	
	Xerox Extensible Interface Platform acts as a gateway, enabling simplified, server-based applications that personalize the user experience through customized touch-screen displays. Personalized for each user. These applications will yield simpler user interactions and result in less time interacting with the MFP which drives increased worker productivity and systems that easily adapt to your business processes.
Machine Specifications	
Accessory Options ⁴	
	High Capacity Feeder Optional 8.5 x 11 / 8.5 x 14 Short Edge Kit for High Capacity Feeder Optional 11 x 17 Short Edge Kit for High Capacity Feeder Offset Catch Tray Office Finisher Convenience Stapler Hole Punch (with Office Finisher) Envelope Tray Kit (in place of Tray 2) Foreign Interface Device (FDI) Walkup Fax with LAN Fax: One line and Two lines Xerox® Scan to PC Desktop® SE and Professional Xerox® Unicode International Printing Kit Common Access Card Enablement 1 GB Memory Kit
Electrical Requirements	
	110-140 Volt Nominal, 60 Hz, 15A Note: Convenience Stapler requires separate 110V 15A
Power Consumption	
	WorkCentre 5755 with Office Finisher
Running	≤ 1330 watts
Standby	≤ 300 watts
Low Power Mode	≤ 125 watts
Auto Off / Sleep mode	≤ 15 watts
Warm up Ready to Copy	≤ 30 seconds
Warm up Ready to Print	≤ 30 seconds
Low Power Recovery	≤ 9 seconds
Environmental Considerations	
Required Temperature Range	50° to 90° F / 10° to 32° C
Required Relative Humidity	10% to 85%

Dimensions and Weights				
	Width ³	Depth	Height	Weight ⁴
Configuration with Offset Catch Tray	51 in. / 1,290 mm	26 in. / 645 mm	45 in. / 1,147 mm	273 lbs / 124 kg
Configuration with Office Finisher	60 in. / 1,524 mm	26 in. / 645 mm	45 in. / 1,147 mm	335 lbs / 152 kg
Noise Levels ⁵				
Standby dB (A) SPL	35			
Run Continuous dB (A) SPL	56			
Run Impulse dB (A) L SPL	61			
Certifications				
	FCC Class A Compliant (US), DOC Class A Compliant (Canada) 2004/108/EC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 2006/95/EC (Europe) 95/5/EEC (Europe) Full system Common Criteria (ISO 15408) Certified			
Supplies				
	Description	Order Number	No. per Box	Expected Yield
	Toner Cartridge ⁶	006R1046	2	> 36,000 per cartridge
	Waste Toner Bottle ⁶ (supplied with each toner cartridge box)	008R12896	1	100,000
	Staple Cartridge (for Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)
	Staple Cartridge (for Convenience Stapler)			
	• Complete Cartridge	008R12964	1	5,000 per cartridge
	• Refill Cartridge	008R12941	3	5,000 per cartridge (15,000 staples)
Xerox® Smart Kits [®]				
	Description	Order Number	No. per Box	Expected Yield
	Fuser Module ⁶ (includes ozone filter)	109R00752	1	400,000
	Xerographic Module ⁶ – Metered	113R00672	1	400,000
	Xerographic Module ⁶ – Sold	113R00674	1	400,000
	Document Handler Feeder Rolls	113R00718	1	150,000 feeds

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

³ Includes Shelf.

⁴ Weights do not include Shelf (2.99 lbs. / 1.36 kg).

⁵ Noise levels shown are “Not to Exceed” levels. Actual noise levels will be lower.

⁶ Approximate pages. Declared Yield based on 5 page job size, 6% area coverage, using letter / A4 media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.

Factory Produced New Model—Xerox classification for equipment that is disassembled, then sent for manufacture as a significantly updated, new generation, per predetermined standards. These units may contain new and reconditioned components that meet Xerox new-product specifications. Each WorkCentre 5755 follows a predetermined manufacturing process and is newly serialized. Devices may or may not contain new software and/or firmware. All our Newly Manufactured and Factory Produced New Model equipment is backed by the Xerox Total Satisfaction Guarantee.



For more information, call **1-800-ASK-XEROX** or visit us at www.xerox.com/office